

Remote indicator for Series 9000, 9200 and IQ8Quad, red



Part-No. 781814

Red prism is continuously or pulsed illuminated by 3 LEDs.

Operating voltage	1,8 V DC
Current consumption	approx. 9 mA
Alarm display	3 red LEDs
Ambient temperature	-25 °C ... 70 °C
Storage temperature	-35 °C ... 85 °C
Type of protection	IP 42
Housing	ABS plastic
Air humidity	< 95 %
Color	white, similar to RAL 9010
Weight	approx. 60 g
Dimensions	W: 85 mm H: 82 mm D: 27 mm

Features:

- 3 continuously or pulsed LEDs
- Power-saving compact indicator



Detectors series 9000

Standard detector base Part No. 781590 and adapter module Part No. 781487 required

Max. 2 detectors per indicator / max. 2 indicator per detector

Remote indicator lights continuously if activated

Detectors series ES Detect

Detector base 805590 required for series ES Detect

Max. 3 detectors per indicator / max. 3 remote indicators per detector

Indicator flashes if activated (Pulse frequency approx.1 Hz)

Detectors series 9200/IQ8Quad / ES Detect

Standard detector base Part No. 781590 or base Part No. 801593 required for series 9200 detectors

Standard base Part No. 805590 required for series IQ8Quad

Max. 1 remote indicator per detector

Max. 60 remote indicators per zone (with max. 30 detectors)

Indicator flashes if activated (Pulse frequency approx.1 Hz)